

Appl. No. 10/672,522
Amdt. dated April 19, 2006
Reply to Office Action of February 6, 2006

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A system, comprising:
a plurality of loads;
a plurality of power supplies coupled to a common power distribution system, the plurality of power supplies are adapted to provide power to said loads; and
control logic coupled to said power supplies, said control logic determines whether output current from a power supply to a load is below a first threshold and, if so, causes one or more power supplies to be disabled;
wherein the control logic continues to disable power supplies until the output current from the power supplies then supplying power to a load is equal to or above said first threshold.
2. (Original) The system of claim 1 wherein said control logic also determines whether output current from at least one of said power supplies exceeds a second threshold and, if so, causes a presently disabled power supply to be enabled.
3. (Canceled).
4. (Original) The system of claim 1 wherein said loads comprise computers.
5. (Currently amended) A system, comprising:
a plurality of servers;
a plurality of power supplies adapted to provide power to said servers via a common distribution system; and

Appl. No. 10/672,522
Amdt. dated April 19, 2006
Reply to Office Action of February 6, 2006

a power supply communication module coupled to said power supplies,
said power supply communication module monitors loads on said
power supplies and disables a power supply if a load is below a first
threshold;

wherein after disabling a power supply, the power supply communication
module monitors the loads on the power supplies presently
supplying power to the servers and disables another power supply if
a load is still below the first threshold.

6. (Canceled).

7. (Currently amended) ~~The system of claim 5~~A system, comprising:
a plurality of servers;
a plurality of power supplies adapted to provide power to said servers via a
common distribution system; and
a power supply communication module coupled to said power supplies,
said power supply communication module monitors loads on said
power supplies and disables a power supply if a load is below a first
threshold, wherein the power supply communication module
enables a presently disabled power supply if a load on a power
supply exceeds a second threshold.

8. (Original) The system of claim 5 wherein the power supply communication
module monitors loads by monitoring the output current of the power supplies.

9. (Original) The system of claim 5 wherein the power supply communication
module couples to the power supplies via a communication bus and requests a
power supply to provide a value indicative of its load via the communication bus.

Appl. No. 10/672,522
Amdt. dated April 19, 2006
Reply to Office Action of February 6, 2006

10. (Currently amended) A system, comprising:
a plurality of loads;
a plurality of power supplies adapted to provide power to said loads via a
common distribution system; and
[[a]] means for determining whether output current from at least one of
said power supplies to a load is below a first threshold and, if so,
causing at least one of said power supplies to be disabled; and
means for continuing to disable power supplies until the output current
from the power supplies presently supplying power to a load is
equal or greater than said first threshold.
11. (Original) The system of claim 10 further including a means for
determining whether output current from at least one of said power supplies
exceeds a second threshold and, if so, causing a presently disabled power supply
to be enabled.
12. (Canceled).
13. (Currently amended) Control logic adapted to dynamically control a
plurality of power supplies, comprising:
a controller; and
memory coupled to said controller;
wherein said controller determines whether output current from at least
one of said power supplies is below a first threshold and, if so,
causing at least one of said power supplies to be disabled, and
wherein said controller continues to disable power supplies until the
output current from the power supplies is equal or greater than said
first threshold.

Appl. No. 10/672,522
Amdt. dated April 19, 2006
Reply to Office Action of February 6, 2006

14. (Original) The control logic of claim 13 wherein said controller also determines whether output current from at least one of said power supplies exceeds a second threshold and, if so, causes a presently disabled power supply to be enabled.

15. (Canceled).

16. (Currently amended) A method usable in a system including a plurality of power supplies which provide power to a plurality electrical devices, comprising:
monitoring the load on each of a plurality of power supplies;
comparing each of the loads to a first threshold; and
disabling a power supply if a load is below said first threshold thereby
causing the load on the remaining power supplies to increase;
wherein disabling a power supply is repeated as long as a load on a power supply is below said first threshold.

17. (Original) The method of claim 16 wherein monitoring the load includes requesting the load to report its output current.

18. (Canceled).

19. (Currently amended) ~~The method of claim 16 further including~~ A method usable in a system including a plurality of power supplies which provide power to a plurality electrical devices, comprising:
monitoring the load on each of a plurality of power supplies;
comparing each of the loads to a first threshold;
disabling a power supply if a load is below said first threshold thereby
causing the load on the remaining power supplies to increase; and
enabling a power supply if a load is greater than a second threshold.

Appl. No. 10/672,522
Amdt. dated April 19, 2006
Reply to Office Action of February 6, 2006

20. (Currently amended) The method of claim ~~[[16]]~~ 19 wherein enabling a power supply is repeated as long as a load on a power supply is above said second threshold.